

ABH-300

Industrial multi-probe monitor · Mapping-grade coverage

ABH-300 family – Industrial multi-channel · Data logger datasheet

Four PT100 channels plus on-board T/RH and barometric pressure — stability chambers, walk-in rooms and mapped ULTs on one instrument.

7 channels	IP65	E-paper	409,600 readings	Battery: ≈82 d USB-loss backup (calc.)
------------	------	---------	------------------	--

Specifications

Product type	Industrial · Wi-Fi monitor
Sensing channels	7 — 4 × probe temperature · Ambient T + RH · Pressure
4 × probe temperature	PT100 Class A via probe board (MAX31865 ×4) · −50...+200 °C
Ambient T + RH	SHT41 · ±0.2 °C typ
Pressure	BMP390 · 300–1250 hPa
Measurement accuracy	±0.15 °C at 0 °C · PT100 Class A (IEC 60751) probe
Display & indication	1.54" e-paper 200 × 200 · −25...+50 °C · holds last reading while asleep
Connectivity	Wi-Fi 2.4 GHz (ESP32-C3-MINI-1U) · MQTT over TLS 1.2+ — Internal FPC · ≤2 dBi
Power	USB 5 V + Molicel P28A 18650 pack (2600 mAh min) · JEITA-gated charging
Battery life	≈82 d USB-loss backup (calculated, spec-compliant logging at firmware defaults; ≈50 d at −20 °C) — Keeps logging through USB-loss
Memory	16 MB W25Q128JV · 409,600 readings · separate never-erased audit region
Sample interval	1 s minimum · configurable
Enclosure	106.4 × 150.0 × 29.3 mm · PC/ABS · UL94 V-0 · UV-stabilised · RAL 7035 grey
Ingress protection	IP65 (design target)
Mounting	Keyhole (2×) + bonded magnets · M12 cable ports
Operating band	−25 to +50 °C (e-paper limit)
Firmware & transport	Signed .abhfw packages · dual-bank A/B · RSA-2048 · trial boot with automatic rollback · MQTT over TLS 1.2+ with per-device credentials (mTLS supported) · X.509 identity
Factory identity	ABH-[model]-[YYWW]-[5-digit sequence] — factory identity written to the ID EEPROM
Ports	4 × M12 probe ports · USB-C
Expansion	J5 FFC-16 accepts Exp-A...F cards

Applications

Cold rooms & large sites	External high-gain antenna (LR) or industrial multi-probe coverage for mapped rooms.
ULT freezers (–80 °C) & dry ice	Logger stays outside the freezer; a Class-A PT100 probe measures inside — accuracy where it matters.
Stability chambers & mapping studies	Four PT100 channels plus T/RH and barometric pressure — one instrument per mapped chamber.

Compatible probes

PRB-PT100-3W — PT100 immersion probe	PRB-PT100-3W-3M · PT100 Class A (IEC 60751:2022) · ± 0.15 °C at 0 °C · –50 to +200 °C
---	---

Part of the Abhilekh platform

One 80 × 50 mm 4-layer platform PCB — 145 parts, single-sided SMT — becomes 20 SKUs by BOM selection and a SKU record in the on-board ID EEPROM.

Firmware updates	Signed .abhfw packages · dual-bank A/B · RSA-2048 · trial boot with automatic rollback
Data transport	MQTT over TLS 1.2+ with per-device credentials (mTLS supported) · X.509 identity
Offline evidence	Plug an offline logger into a PC and it enumerates a FAT16 drive with README.TXT, DATA.CSV and an ECDSA P-256-signed REPORT.PDF — a self-verifying trip record.
Calibration	Probe channel templates live in the ID EEPROM; the platform tracks NIST-traceable calibration certificates, due dates and reminders per probe.
Certification roadmap	EN 12830:2018 — temperature recorders · CE — RED / EMC / safety · FCC Part 15 · WHO PQS E006 — vaccine cold chain · IEC 61010-1 / IEC 62368-1 · UN 38.3 / IEC 62133-2 — cells & packs — targets, not held certificates

The ABH line is at the design-frozen, pre-production stage: every enclosure has passed generated fit-check geometry (791/791 checks, 20/20 SKUs) and every battery-life, drop, thermal and IP figure shown is a calculated or simulated design estimate — measured values replace them as validation hardware runs. Regulatory marks above are the certification roadmap, not held certificates.

Neodrics Technologies · Vadodara & Gandhinagar, Gujarat, India · info@neodrics.com · <https://neodrics.com>